

IN THE CLAIMS

This listing of claims replaces all prior versions and listings of claims in the application.

Listing of Claims:

1 (Currently Amended). A recording medium to/from which data can be written/read by a data processing apparatus, comprising:

a host interface operable to communicate with the data processing apparatus;

a data storage section having plural recording regions to store data;

a region information storage section that stores information about each recording region of the data storage section, the region information storage section stores information about an address attribute of each recording region of the data storage section, the address attribute being a unit of address specified by the data processing apparatus for access to the recording region of the recording medium; and

a controller operable to receive a command for instructing writing or reading of data from the data processing apparatus by way of the host interface, and when the received command specifies an address indicating an access region, the controller being operable to judge a unit of the address specified by the received command, on the basis of the address attribute stored in the region information storage section,

wherein the region information storage section further stores information about a type of format for the command received in the host interface.

2 (Cancelled).

3 (Previously Presented). The recording medium according to claim 1, wherein the unit of address is a sector or a byte.

4 (Cancelled).

5 (Previously Presented). The recording medium according to claim 1, wherein data stored in each recording region is managed by a file system corresponding to each recording region.

6 (Previously Presented). The recording medium according to claim 1, wherein the region information storage section further stores information about type of command set of the command received in the host interface.

7 (Cancelled).

8 (Previously Presented). The recording medium according to claim 1, further comprising a controller operable to receive, from the data processing apparatus by way of the host interface, a command to set an accessible recording region in the data storage section from the data processing apparatus, set an accessible region in the region information storage section according to the received command when the received command specifies the address attribute of the recording region set to be accessible, and change the address attribute of the set accessible region.

9 (Previously Presented). The recording medium according to claim 1, further comprising a controller operable to, when receiving a command for changing size of recording region in the data storage section through the host interface from the data processing apparatus, change size of recording region according to the received command, determine the address attribute of the changed recording region according to the changed size of the recording region, and update the region information storage section using the determined address attribute.

10 (Currently Amended). A control method of a recording medium having a data storage region for storing data, the data storage region being accessible from outside for writing and reading data, the control method comprising:

dividing the data storage region of the recording medium into plural recording regions;

storing region information which is information about each divided recording region to a predetermined region in the recording medium;

receiving a command for instructing writing or reading of data, with an address showing an access range specified in the command; and

judging a unit of the address specified by the received command, on the basis of a stored address attribute, to specify an access range,

wherein the region information includes information about the address attribute of each recording region, the address attribute being a unit of address specified for access to the recording region of the recording medium, and

wherein the region information further stores information about a type of format for the received command.

11 (Cancelled).

12 (Previously Presented). The control method according to claim 10, wherein the unit of address is a sector or a byte.

13 (Cancelled).

14 (Previously Presented). The control method according to claim 10, wherein data stored in each recording region is managed by a file system corresponding to each recording region.

15 (Previously Presented). The control method according to claim 10, wherein the region information further stores information about type of command set of the received command.

16 (Cancelled).

17 (Previously Presented). The control method according to claim 10, wherein the region information includes information of a recording region accessible from outside, and the control method further comprises:

receiving a command for setting a recording region accessible from outside, the command specifying the address attribute of the accessible recording region, and

in the region information, setting the accessible recording region and changing the information about the address attribute of the set accessible recording region, according to the received command.

18 (Previously Presented). The control method according to claim 10, wherein the region information further includes size of each recording region, and the control method further comprises:

- receiving a command for changing size of recording region of the recording medium;
- changing the size of recording region according to the received command; and
- determining the address attribute of a changed recording region according to the changed size of recording region, and updating the region information using the determined address attribute.